













Up to 2800MB/s

Four M.2 SSD Slots

RAID Ready

DisplayPort

Thunderbolt 3

Mac & Windows

owc Express 4M2

Thunderbolt 3

Infinitely Configurable. Infinitely Reconfigurable.

Small in stature. Big on capability. The Express 4M2 is ready to serve with four easy-to-access M.2 NVMe SSD slots customizable for any workflow with vibration damping feet that allow for vertical or horizontal orientation. Install up to 16TB capacity and experience up to 2800MB/s of mind-bending performance via Thunderbolt 3. The Express 4M2 is an amazingly small digital workhorse with world-renowned OWC quality and award-winning support built in.

Ingest and duplicate dailies at breakneck speeds, work with higher resolutions, smoothly scrub through demanding timelines, and plow through thousands of photos with ease. The Express 4M2 is one seriously fast drive to have by your side to take digital capabilities to a new level.

Key Features

- Up to 16TB
- Up to 2800MB/s Thunderbolt 3 performance
- Four M.2 NVMe SSD slots
- Compact design positions vertically or horizontally
- DisplayPort connection
- Advanced SoftRAID engine
- Thunderbolt Certified for Mac and Windows
- Thunderbolt 3 cable included













PART NUMBER	CAPACITY	UPC	AVAILABLE
OWC Express 4M2			
OWCTB3EX4M2SL	0GB	810586030090	now

OWC Express 4M2

Thunderbolt 3

Tech Specs

Interface

- Thunderbolt 3

Device Ports

- (2) Thunderbolt 3 (USB Type-C)
- (1) DisplayPort 1.2*

Display Support

- 4K @ 60Hz

Drive Slots

- (4) M.2-2280 "M Key" (PCle 3.0 x1)

Drive Support

- M.2 NVMe
- M.2 AHCI (PCIe only)

Bootable

- Mac: macOS 10.12 or later**
- Windows: Booting not supported

System Requirements

- Any computer with a native Thunderbolt 3 port
- Mac: macOS 10.12 or later**
- Windows: Windows 10 or later

Power Supply

- External UL-listed, universal auto-switching
- AC input: 110 ~ 240V, 50/60Hz
- DC output: 12V 7.5A
- Total wattage: 90W

Includes

- OWC Express 4M2
- Quick start guide
- Thunderbolt 3 cable (40Gb/s)
- External power supply and cable
- SoftRAID Lite XT

Warranty

- 1 Year OWC Limited Warranty

Enclosure Dimensions

- 5.1 in (W) x 2.0 in (H) x 3.3 in (D)
- 13.0 cm (W) x 5.0 cm (H) x 8.5 cm (D)

Enclosure Weight (empty)

- 1.9 lb (0.8 kg)



^{*} Does not support Dual-Mode DisplayPort (DP++). Adaptable to HDMI, DVI, and VGA via active adapters. Supports Multi-Stream Transport (MST), although MST is not currently supported by macOS. **SSDs using 512b sector sizes require macOS 10.13 or later